

# 装载机 WHEEL LOADER

型号 Model : ZL18-30

## 优势 Advantage (Features)

1. Hangzhou Advance Gear group WG180 torque converter and fix-shaft gearbox , with ZF technology
2. Single lever pilot control system makes operation easy and comfortable
3. Strengthened axles owns large bearing capacities and high reliability
4. Twin pump merging hydraulic system makes lower consumption and excellent performance
5. The coaxes flow -amplified ,hydraulic compensated steering makes operation easy and performance reliable
6. Air over hydraulic brake system ;eight caliper disc brakes
7. Main articulated points take sealed ,lubricated ,dust -proof layers, which owns good durability

## 具体参数 Specification

型号	Model	ZL18	ZL20	ZL25	ZL30	ZL30A
额定装载质量	Rated weight	1800KG	2000KG	2500KG	3000KG	3000KG
额定斗容量	Rated capacity	1.03m <sup>3</sup>	1.3m <sup>3</sup>	1.6m <sup>3</sup>	1.7m <sup>3</sup>	1.7m <sup>3</sup>
整机重量	Operating weight	5000KG	6000KG	748KG	9500KG	9500KG
额定功率	Rated power	55KW	60KW	75KW	85KW	92KW
额定转速	Rated speed	2400rpm	2400r/min	2400r/min	2300r/min	2300r/min
卸载高度	Max .dump height	2800mm	2800mm	3200mm	3250mm	3250mm
卸载距离	Max .dump reach	885mm	930mm	1045mm	1200mm	1200mm
最小离地间隙	Min .ground clearance	310mm	310mm	310mm	380mm	380mm
轴距	Wheel base	2150mm	2190mm	2280mm	2760mm	2760mm
轮距	Tread	1080mm	1380mm	1440mm	1800mm	1800mm
铲斗提升时间	Lifting time	4s	Total time:9.8s	Total time:11.3s	Total time:11s	Total time:11s
铲斗下降时间	Lowering time	3s				
卸料时间	Unloading time	2s				
最大掘起力	Max.breakout force	49KN	65KN	86KN	138KN	138KN
最小转弯半径	Min.turning radius	3500mm	4239mm	4500mm	5700mm	5700mm
整机尺寸 (长*宽*高)	Overall dimensions (length*width*height)	5800*1730*2800 mm	5910x1910x2810 mm	6150x1970x3000 mm	7050x2430x3120 mm	7050x2430x3120 mm
可选发动机	Engine option :	1. 潍坊 WeiFang ZH4102 2. 潍柴华丰 WeiChai HuaFeng ZH402GG41	1. 潍坊 WeiFang ZH4102. 2. 潍柴华丰 WeiChai Cummins 4BT3.9	1. 洛拖 LuoTuo YTR4108. 2. 锡柴 XinChai 4105 3. 康明斯 Cummins 4BT3.9	1. 锡柴 XiChai 6110 2. 康明斯 Cummins 6BT5.9	1. 锡柴 XiChai 6110 2. 潍柴 WeiChai 6105 3. 康明斯 Cummins 6BT5.9 4. 道依茨 Deutz TD226B